



[Brock's Performance](#) • 4064 E. Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062

PAIR BLOCK-OFF INSTRUCTIONS FOR YAMAHA FZ-09 (14-)

The PAIR block-off cap is used to block off emissions (PAIR) to help prevent 'deceleration pop' and also prevents ram-air pressure loss from the air box after blocking the PAIR. It will be necessary to remove the fuel tank to access the PAIR valve hose. Refer to a factory service manual for more detailed information.

1. Remove the seat, the fuel tank cover, and then remove the fuel tank to fully access the air box.
2. Locate the PAIR valve hose on the left side of the air box, shown in (Figure 1).
3. Using a pair of pliers squeeze the clamp on the hose and pull it down.
4. Pull the hose off of the air box port and press the cap one (1) inch into the hose. Wet the cap a little with Windex or WD-40 and use a 3/8" drive extension or sharpie marker to push it in (Figure 2).
5. Push the hose back onto the port on the air box and secure with clamp.
6. Reinstall fuel tank, tank cover, and seat.



All Brock's Performance products are designed for closed-course racetrack use ONLY!

For more information on Brock's Performance Warranty and Terms and Conditions: www.BrocksPerformance.com
> About Us > Terms and Conditions

For Questions and Comments: www.BrocksPerformance.com > Customer Service > Contact Us
or call the Tech Line 937-912-0054