

# Brock's

## PERFORMANCE

Brock's Performance • 4064 E. Patterson Rd • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062

### Installation Instructions for CT Series™ Noise Reduction Plug

The Noise Reduction Plug for Brock's Performance CT Series™ titanium exhaust systems are used to reduce the noise level of the exhaust system. Our Noise Reduction Plugs are easily installed/uninstalled to temper the edge without significantly affecting the rich tone of our exhaust systems. Also, due to our free flow design, no map changes are required.

1. Remove mounting bolt from the muffler.
2. Remove springs from the muffler.
3. Slide muffler off of the pipe.
4. Insert the noise reduction plug into the pipe. *See Figure 1 & 2*
5. Replace the muffler and springs.
6. Reinstall the mounting bolt.
7. Repeat steps 1-6 for a dual system.



**All Brock's Performance products are designed for closed-course race track use ONLY!**

**For more information on Brock's Performance Warranty and Terms and Conditions:**

[www.BrocksPerformance.com](http://www.BrocksPerformance.com) > About Us > Terms and Conditions

**For Questions and Comments:**

[www.BrocksPerformance.com](http://www.BrocksPerformance.com) > Customer Service > Contact Us, or call the Tech Line 937-912-0054