



[Brock's Performance](#) • 4064 E. Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062

## Harley-Davidson® Touring (14-16) S&S Stealth Air Cleaner Spacer Kit Instructions

**The spacer kit (Figure 1) is designed to allow the use of the OEM air cleaner cover on Harley-Davidson® Touring Models (14-16) in conjunction with the S&S Stealth Air Cleaner Kits**

- The supplied spacer kit (Figure 1) will be used in place of the 5/16" button head screw (Figure 2) included with the S&S stealth air cleaner kit (this screw is no longer required)
- Place the washer onto the bolt
- Insert the bolt/washer assembly through the front-side of the OEM air cleaner cover
- Place the spacer over the bolt on the backside of the OEM air cleaner cover
- Apply a small amount of 243 blue Loctite to the bolt threads
- Install the air cleaner cover/spacer kit assembly on to the plastic top filter plate and torque to 10 ft.-lbs.



**Fig 1**



**Fig 2**

**All Brock's Performance products are designed for closed-course racetrack use ONLY!**

For more information on Brock's Performance Warranty and Terms and Conditions: [www.BrocksPerformance.com](http://www.BrocksPerformance.com)  
> About Us > Terms and Conditions

For Questions and Comments: [www.BrocksPerformance.com](http://www.BrocksPerformance.com) > Customer Service > Contact Us  
or call the Tech Line 937-912-0054